



TC

[illegible]

Model		Bearing	Rated Voltage	Startup Voltage	Current	Power	Speed	Air Flow		Static Pressure		Noise
型号		轴承	额定电压	启动电压	电流	功率	转速	风量		风压		噪音
Part NO.	Function	System	VDC	VDC	A	W	RPM	M³/min	CFM	mmH₂O	INH₂O	dBA
HBH7512HC		Hydraulic	12	9.5	0.30	3.60	4000	0.26	9.18	21.42	0.84	36.0
HBH7512MC				9.5	0.25	3.00	3500	0.23	8.03	16.4	0.65	33.1
HBH7512LC				9.5	0.20	2.40	3000	0.19	6.89	12.05	0.47	29.8
HBB7512HC		Ball		9.5	0.30	3.60	4000	0.26	9.18	21.42	0.84	36.0
HBB7512MC				9.5	0.25	3.00	3500	0.23	8.03	16.4	0.65	33.1
HBB7512LC				9.5	0.20	2.40	3000	0.19	6.89	12.05	0.47	29.8
HBH7524HC		Hydraulic	24	12.0	0.25	6.00	4000	0.26	9.18	21.42	0.84	36.0
HBH7524MC				12.0	0.20	4.80	3500	0.23	8.03	16.4	0.65	33.1
HBH7524LC				12.0	0.15	3.60	3000	0.19	6.89	12.05	0.47	29.8
HBB7524HC		Ball		12.0	0.25	6.00	4000	0.26	9.18	21.42	0.84	36.0
HBB7524MC				12.0	0.20	4.80	3500	0.23	8.03	16.4	0.65	33.1
HBB7524LC				12.0	0.15	3.60	3000	0.19	6.89	12.05	0.47	29.8