



DC-直流轴流风扇 200x200x60mm

马达可选功能列表 (Available Functions)

1. 马达保护 (Moto protection)

AS

2. 信号输出 (Signal out put)

FG

RD


3. 调速方式 (Speed control mode)

PWM


TC



风扇P-Q曲线 / Fan performance curve



尺寸图 / Dimension drawing



Model		Bearing	Rated Voltage	Startup Voltage	Current	Power	Speed	Air Flow		Static Pressure		Noise
型号		轴承	额定电压	启动电压	电流	功率	转速	风量		风压		噪音
Part NO.	Function	System	VDC	VDC	A	W	RPM	M ³ /min	CFM	mmH ₂ O	INH ₂ O	dBA
HDB20024HW	-A	Ball	24	18.0	3.20	76.80	3200	16.63	587.60	20.00	0.79	66.0
HDB20024MW	-A	Ball		18.0	1.46	35.04	2600	13.51	477.40	13.20	0.52	59.0
HDB20024LW	-A	Ball		18.0	0.66	15.84	2000	10.39	367.30	7.80	0.31	52.0
HDB20048HW	-A	Ball	48	24.0	1.60	76.80	3200	16.63	587.60	20.00	0.79	66.0
HDB20048MW	-A	Ball		24.0	0.73	35.04	2600	13.51	477.40	13.20	0.52	59.0
HDB20048LW	-A	Ball		24.0	0.33	15.84	2000	10.39	367.30	7.80	0.31	52.0